Page 1/9



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.12.2014

Version number 2

Revision: 18.12.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: MARABU Do-it Gl.-silber, Gl-gold

· Article number: 210606982, -984

 \cdot 1.2 Relevant identified uses of the substance or mixture and uses advised against --

• Application of the substance / the mixture Lacquer

1.3 Details of the supplier of the safety data sheet
Manufacturer/Supplier: Marabu GmbH & Co KG Asperger Straße 4 D-71732 Tamm Telefon-Nr. (++49)-7141/691-0 Fax-Nr. (++49)-7141/691-117 PRSI@marabu.de

• Further information obtainable from: Produktsicherheit 07141/691-116 oder 232

· 1.4 Emergency telephone number: 0621-60-43333

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

GHS07

Acute Tox. 4	H312	Harmful in contact with skin.
Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.

 \cdot Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xn; Harmful

R20/21: Harmful by inhalation and in contact with skin.

Xi; Irritant

R38:

F+; Extremely flammable

Irritating to skin.

R12: Extremely flammable.

• Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. Warning! Pressurized container.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)

iВ・

Page 2/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.12.2014

Version number 2

Revision: 18.12.2014

Trade name: MARABU Do-it Gl.-silber, Gl-gold

	(Contd. of page
· 2.2 Lahe	l elements
	g according to Regulation (EC) No 1272/2008
	luct is classified and labelled according to the CLP regulation.
	pictograms
•	A
, the	
(()	
	\mathbf{V}
GHS02	GHS07
· Signal w	ord Danger
Hazard-	determining components of labelling:
	ixture of isomers
ethylben.	
	statements
	229 Extremely flammable aerosol. Pressurised container: May burst if heated.
	332 Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
· Precauti	onary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves.
P410+P	412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents / container in accordance with regional regulations.
	al information:
Buildup	of explosive mixtures possible without sufficient ventilation.
	a han anda
• 2.3 Othe	r nazaras of PBT and vPvB assessment

· **vPvB:** Not applicable.

*

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterization: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

• Dangerous components:		
CAS: 1330-20-7	xylene, mixture of isomers	25-<50%
EINECS: 215-535-7	🗙 Xn R20/21; 🗙 Xi R38	
Index number: 601-022-00-9		
Reg.nr.: 01-2119488216-32	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	-
CAS: 74-98-6	propane	12.5-<20%
EINECS: 200-827-9	F + R12	
Index number: 601-003-00-5	🔞 Flam. Gas 1, H220; Press. Gas, H280	-
Reg.nr.: 01-2119486944-21		
	•	(Contd. on page 3)
		CD

Printing date 18.12.2014

Version number 2

Revision: 18.12.2014

Trade name: MARABU Do-it Gl.-silber, Gl-gold

		(Contd. of page 2)
CAS: 106-97-8	butane	12.5-<20%
EINECS: 203-448-7	F + R12	
Index number: 601-004-00-0	🐼 Flam. Gas 1, H220; Press. Gas, H280	-
Reg.nr.: 01-2119474691-32		
CAS: 75-28-5	isobutane	2.5-<5.0%
EINECS: 200-857-2	F + R12	
Index number: 601-004-00-0	🔞 Flam. Gas 1, H220; Press. Gas, H280	-
Reg.nr.: 01-2119485395-27		
CAS: 100-41-4	ethylbenzene	2.5-<5.0%
EINECS: 202-849-4	Xn R20-48/20-65; 🔥 F R11	
Index number: 601-023-00-4	🔞 Flam. Liq. 2, H225; 🔕 STOT RE 2, H373; Asp. Tox. 1,	-
Reg.nr.: 01-2119489370-35	H304; 🚸 Acute Tox. 4, H332; Aquatic Chronic 3, H412	
CAS: 7429-90-5	aluminium powder (pyrophoric)	<2.5%
EINECS: 231-072-3	F R15-17	
Index number: 013-001-00-6		-
Reg.nr.: 01-2119529243-45		
A J Jidi an al informa adiana	1	

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1 67/548 EU), so the classification as carcinogen need not to apply. For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, bluspoeder of waterstraal. Grotere brand met waterstraal of met schuim. Vaten met water afkoelen.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 4)

G

Printing date 18.12.2014

Version number 2

Revision: 18.12.2014

(Contd. of page 3)

Trade name: MARABU Do-it Gl.-silber, Gl-gold

Do not allow to enter sewers/ surface or ground water. Do not allow product to reach sewage system or any water course. • **6.3 Methods and material for containment and cleaning up:** Do not flush with water or aqueous cleansing agents Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location. Observe official regulations on storing packagings with pressurized containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Do not seal receptacle gas tight.
 Store in cool, dry conditions in well sealed receptacles.
 Protect from heat and direct sunlight.
- · Storage class: 2B

010 11

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 C	· 8.1 Control parameters					
· Ingre	\cdot Ingredients with limit values that require monitoring at the workplace:					
1330-	1330-20-7 xylene, mixture of isomers					
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm					
	Sk; BMGV					
106-9	7-8 butane					
WEL	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)					
100-4	1-4 ethylbenzene					
WEL	Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk					
7429-	90-5 aluminium powder (pyrophoric)					
WEL	Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust					
	(Contd. on page 5)					
	G					

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.12.2014

Version number 2

Revision: 18.12.2014

Trade name: MARABU Do-it Gl.-silber, Gl-gold

 Ingredients with biological limit val 	ues:	
1000 00 7 1 1 ()		
1330-20-7 xylene, mixture of isomer	rs	
BMGV 650 mmol/mol creatinine		
Medium: urine		
Sampling time: post shift	:1	
Parameter: methyl hippuric		
Additional information: The lists va	lid during the making were used as basis.	
8.2 Exposure controls		
Personal protective equipment:		
· General protective and hygienic measures:		
Keep away from foodstuffs, beverage		
Immediately remove all soiled and co		
Wash hands before breaks and at the		
Do not inhale gases / fumes / aeroso Avoid contact with the skin.	lS.	
Avoid contact with the eyes and skin.		
Respiratory protection:		
Not necessary if room is well-ventila	ted	
Otherwise, filter class A / P2 or self		
Protection of hands:		
Protective gloves		
Solvent resistant gloves		
	protective gloves made of butyl shoud be used (min. 0.4 mm thick), e.	
KCL Camatril, article no. 898 or sin		
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and th		
		selection of the glove material of
degradation	i constactation of the penetration times, takes of affasion and th	
degradation	i constactation of the penetration times, rates of allfusion and th	
degradation Material of gloves Butyl rubber, BR Penetration time of glove material		
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness		
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min		
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min Butyl acetate: 60 min		
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min		
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min		
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min		
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min		
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min	of 0.4 mm are resistant to:	
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min Eye protection: Safety glasses SECTION 9: Physical and ch	of 0.4 mm are resistant to: emical properties	
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min Eye protection: Safety glasses SECTION 9: Physical and ch 9.1 Information on basic physical a	of 0.4 mm are resistant to: emical properties	
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min Eye protection: Safety glasses SECTION 9: Physical and ch 9.1 Information on basic physical a General Information	of 0.4 mm are resistant to: emical properties	
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min Eye protection: Safety glasses SECTION 9: Physical and ch 9.1 Information on basic physical a General Information	of 0.4 mm are resistant to: emical properties	
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min Eye protection: Safety glasses SECTION 9: Physical and ch 9.1 Information on basic physical a General Information Appearance:	of 0.4 mm are resistant to: emical properties nd chemical properties	
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min Eye protection: Safety glasses SECTION 9: Physical and ch 9.1 Information on basic physical a General Information Appearance: Form:	of 0.4 mm are resistant to: emical properties nd chemical properties Aerosol	
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min Eye protection: Safety glasses SECTION 9: Physical and ch 9.1 Information on basic physical a General Information Appearance: Form: Colour: Odour:	of 0.4 mm are resistant to: emical properties nd chemical properties Aerosol Silver-coloured	
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min Eye protection: Safety glasses SECTION 9: Physical and ch 9.1 Information on basic physical a General Information Appearance: Form: Colour:	of 0.4 mm are resistant to: emical properties nd chemical properties Aerosol Silver-coloured Characteristic	
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min Eye protection: Safety glasses SECTION 9: Physical and ch 9.1 Information on basic physical a General Information Appearance: Form: Colour: Odour: Odour threshold:	of 0.4 mm are resistant to: emical properties nd chemical properties Aerosol Silver-coloured Characteristic Not determined.	
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min Eye protection: Safety glasses SECTION 9: Physical and ch 9.1 Information on basic physical a General Information Appearance: Form: Colour: Odour: Odour threshold: pH-value:	of 0.4 mm are resistant to: emical properties nd chemical properties Aerosol Silver-coloured Characteristic Not determined.	
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min Eye protection: Safety glasses SECTION 9: Physical and ch 9.1 Information on basic physical a General Information Appearance: Form: Colour: Odour: Odour threshold: pH-value: Change in condition	of 0.4 mm are resistant to: emical properties nd chemical properties Aerosol Silver-coloured Characteristic Not determined. Not determined.	
degradation Material of gloves Butyl rubber, BR Penetration time of glove material Butyl rubber gloves with a thickness Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min Eye protection: Safety glasses SECTION 9: Physical and ch 9.1 Information on basic physical a General Information Appearance: Form: Colour: Odour: Odour threshold: pH-value: Change in condition Melting point/Melting range:	of 0.4 mm are resistant to: emical properties nd chemical properties Aerosol Silver-coloured Characteristic Not determined. Not determined. Undetermined.	

(Contd. on page 6)

GB

Page 6/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.12.2014

Version number 2

Revision: 18.12.2014

Trade name: MARABU Do-it Gl.-silber, Gl-gold

	(Contd. of page
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	365 °C
• Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
• Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	1.0 Vol %
Upper:	10.9 Vol %
· Vapour pressure at 20 •C:	8300 hPa
Density at 20 °C:	$0.71 \ g/cm^3$
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wa	ter): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC-(EU)	
	566.6 g/l
· VOC-EU%	79.81 %
· Solids content:	18.5 %
• 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity:

· LD/LC50	values	relevant	for c	lassification:
-----------	--------	----------	-------	----------------

1330-20-7 xylene, mixture of isomers				
	LD50	8700 mg/kg (rat)		
Dermal	LD50	8700 mg/kg (rat) >2000 mg/kg (rabbit)		
Inhalative	LC50/4 h	6350 mg/l (rat)		

[·] Primary irritant effect:

• on the eye: No irritating effect.

(Contd. on page 7)

[•] on the skin: Irritant to skin and mucous membranes.

GB

Printing date 18.12.2014

Version number 2

Revision: 18.12.2014

(Contd. of page 6)

Trade name: MARABU Do-it Gl.-silber, Gl-gold

- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Harmful

Irritant

Vapours have narcotic effect.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

1330-20-7 xylene, mixture of isomers

EC50 (24*h*) >175 *mg/l* (bacteria)

EC50 / 48h 3.82 mg/l (daphnia magna / Wasserfloh)

EC50/72h 4.7 mg/l (Pseudokirchneriella subcapitata)

LC50/96h 7.6 mg/l (oncorhynchus mykiss / Regenbogenforelle)

· 12.2 Persistence and degradability No further relevant information available.

· 12.3 Bioaccumulative potential No further relevant information available.

- 12.4 Mobility in soil No further relevant information available.
- \cdot Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

15 01 04 metallic packaging

15 01 11* metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR	UN1950 AEROSOLS	
IMDG	AEROSOLS	

Printing date 18.12.2014

Version number 2

Revision: 18.12.2014

Trade name: MARABU Do-it Gl.-silber, Gl-gold

	(Contd. of	page
IATA	AEROSOLS, flammable	
14.3 Transport hazard class(es)		
ADR		
A		
2		
Class	2 5F Gases.	
Label	2.1 2.1	
IMDG, IATA		
<u> </u>		
Class	2.1	
Label	2.1	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Warning: Gases.	
Danger code (Kemler):	-	
EMS Number:	F-D,S-U	
14.7 Transport in bulk according to Anne		
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:		
ADR		
Limited quantities (LQ)	1L Contra EQ	
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity	
Transport category	2	
Tunnel restriction code	D	
IMDG		
Limited quantities (LQ)	1L	
Excepted quantities (EQ)	Code: E0	
	Not permitted as Excepted Quantity	
UN "Model Regulation":	UN1950, AEROSOLS, 2.1	

SECTION 15: Regulatory information

*

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture .

• Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9) GB Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.12.2014

Version number 2

Revision: 18.12.2014

GB

Trade name: MARABU Do-it Gl.-silber, Gl-gold

	(Contd. of page 8)
Relevan	nt phrases
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
	Flammable liquid and vapour.
	Catches fire spontaneously if exposed to air.
	In contact with water releases flammable gases.
	Contains gas under pressure; may explode if heated.
	May be fatal if swallowed and enters airways.
	Harmful in contact with skin.
	Causes skin irritation.
	Harmful if inhaled.
	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
R10	Flammable.
	Highly flammable.
	Extremely flammable.
	Contact with water liberates extremely flammable gases.
	Spontaneously flammable in air.
	Harmful by inhalation.
	Harmful by inhalation and in contact with skin.
	Irritating to skin.
	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
	Harmfull: may cause lung damage if swallowed
Contaci	t: DiplChem. G. Heller oder DiplIng. U. Voetter
Abbrevi	iations and acronyms:
	lement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the
	nal Transport of Dangerous Goods by Rail)
	R: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
	ternational Civil Aviation Organization cord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International
	of Dangerous Goods by Road)
	ternational Maritime Code for Dangerous Goods
IATA: Int	ernational Air Transport Association
	bally Harmonized System of Classification and Labelling of Chemicals
	European Inventory of Existing Commercial Chemical Substances
	European List of Notified Chemical Substances mical Abstracts Service (division of the American Chemical Society)
	atile Organic Compounds (USA, EU)
	thal concentration, 50 percent
	thal dose, 50 percent
Flam. Ga	s 1: Flammable gases, Hazard Category 1
	rosol 1: Flammable aerosols, Hazard Category 1
	s: Gases under pressure: Compressed gas
	. 2: Flammable liquids, Hazard Category 2 . 3: Flammable liquids, Hazard Category 3
	1: Pyorphoric Solids, Hazard Category 1
	act. 2: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 2
Acute Tox	r. 4: Acute toxicity, Hazard Category 4
Skin Irrit.	2: Skin corrosion/irritation, Hazard Category 2
	2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
	1: Aspiration hazard, Hazard Category 1
Aquatic C	Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3