Printing date 18.12.2014 Version number 5 Revision: 18.12.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MARABU Glitterspray
- · Article number: 2106 06 582, 2106 06 584
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against --
- · Application of the substance / the mixture Lacquer
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Marabu GmbH & Co KG

Asperger Straße 4 D-71732 Tamm

Telefon-Nr. (++49)-7141/691-0

Fax-Nr. (++49)-7141/691-117

PRSI@marabu.de

- · Further information obtainable from: Produktsicherheit 07141/691-116 oder 232
- · 1.4 Emergency telephone number: 0621-60-43333

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R38: Irritating to skin.



F+; Extremely flammable

R12: Extr

Extremely flammable.



N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

(Contd. on page 2)

Printing date 18.12.2014 Version number 5 Revision: 18.12.2014

Trade name: MARABU Glitterspray

(Contd. of page 1)

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

Has a narcotizing effect.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

GHS09

· Signal word Danger

· Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents / container in accordance with regional regulations.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 64742-49-0 EINECS: 265-151-9 Index number: 649-328-00-1

Reg.nr.: 01-2119475133-43

Naphtha (petroleum), hydrotreated light

🗶 Xn R65; χ Xi R38; 👔 F R11; 🖐 N R51/53

🚸 Flam. Liq. 2, H225; & Asp. Tox. 1, H304; 体 Aquatic Chronic 2, H411; (1) Skin Irrit. 2, H315; STOT SE 3, H336

(Contd. on page 3)

25-<50%

Printing date 18.12.2014 Version number 5 Revision: 18.12.2014

Trade name: MARABU Glitterspray

	(Co	ontd. of page 2)
CAS: 106-97-8	butane	25-<50%
EINECS: 203-448-7	♦ F+ R12	
Index number: 601-004-00-0	Tlam. Gas 1, H220; Press. Gas, H280	
Reg.nr.: 01-2119474691-32		
CAS: 115-10-6	dimethyl ether	25-<50%
EINECS: 204-065-8	♦ F+ R12	
Index number: 603-019-00-8	♦ Flam. Gas 1, H220; Press. Gas, H280]
Reg.nr.: 01-2119472128-37		
	Epoxydharz	≤0.5%
	😡 T R25; 🗙 Xn R20/21; 🗙 Xi R36/37/38	
	♠ Flam. Liq. 3, H226; ♠ Acute Tox. 3, H301; ♠ Acute Tox. 4,	1
	H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319;	
	STOT SE 3, H335	

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1 67/548 EU), so the classification as carcinogen need not to apply.

For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, bluspoeder of waterstraal. Grotere brand met waterstraal of met schuim.

Vaten met water afkoelen.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

Do not allow product to reach sewage system or any water course.

- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 18.12.2014 Version number 5 Revision: 18.12.2014

Trade name: MARABU Glitterspray

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- · Storage class: 2B
- \cdot 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

Not necessary if room is well-ventilated.

Otherwise, filter class A / P2 or self contained.

(Contd. on page 5)

Printing date 18.12.2014 Version number 5 Revision: 18.12.2014

Trade name: MARABU Glitterspray

· Protection of hands:

(Contd. of page 4)



Protective gloves

Solvent resistant gloves

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Butyl rubber, BR
- · Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

· Eye protection: Safety glasses

CECTION	0. DI	and a al	are do	la arresta al	TOTAL OTTO OTTO
SECTION	y: rr	lysicai	ana c	<u>nemicai</u>	properties

SECTION 7.1 Hysical and encontent properties				
· 9.1 Information on basic physical and chemical properties				
· General Information				
· Appearance:				
Form:	Aerosol			
Colour:	According to product specification			
· Odour:	Characteristic			
· Odour threshold:	Not determined.			
· pH-value:	Not determined.			
· Change in condition				
Melting point/Melting range:	Undetermined.			
Boiling point/Boiling range:	Not applicable, as aerosol.			
· Flash point:	Not applicable, as aerosol.			
· Flammability (solid, gaseous):	Not applicable.			
· Ignition temperature:	235 °C			
· Decomposition temperature:	Not determined.			
· Self-igniting:	Product is not selfigniting.			
· Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.			
· Explosion limits:				
Lower:	1.5 Vol %			
Upper:	18.6 Vol %			
· Vapour pressure at 20 °C:	5200 hPa			
· Density at 20 °C:	$0.68 \ g/cm^3$			
· Relative density	Not determined.			
· Vapour density	Not determined.			
· Evaporation rate	Not applicable.			
· Solubility in / Miscibility with				
water:	Not miscible or difficult to mix.			

(Contd. on page 6)

Printing date 18.12.2014 Version number 5 Revision: 18.12.2014

Trade name: MARABU Glitterspray

		(Contd. of page
· Partition coefficient (n-octano	l/water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
VOC- (EU)		
	647.6 g/l	
· VOC-EU%	95.48 %	
· Solids content:	3.7 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Vapours have narcotic effect.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- $\cdot \textit{Additional ecological information:}$
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 7)

Printing date 18.12.2014 Version number 5 Revision: 18.12.2014

Trade name: MARABU Glitterspray

(Contd. of page 6)

- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue			
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances		
15 01 04	metallic packaging		
	metallic packaging containing a dangerous solid porous matrix (for example asbestos), including		
	empty pressure containers		

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number	
· 14.1 ON-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name	
· ADR	UN1950 AEROSOLS, ENVIRONMENTAL HAZARDOUS
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
$\cdot ADR$	
· Class	2 5F Gases.
· Label	2.1
· IMDG, IATA	
· Class	2.1
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Gases.
· Danger code (Kemler):	-
· EMS Number:	F- D , S - U

(Contd. on page 8)

Printing date 18.12.2014 Version number 5 Revision: 18.12.2014

Trade name: MARABU Glitterspray

· 14.7 Transport in bulk according to Anne	ex II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· <i>ADR</i>	
· Limited quantities (LQ)	IL
\cdot Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
\cdot Excepted quantities (EQ)	Code: E0
· · · · · · · · · · · · · · · ·	Not permitted as Excepted Quantity
· UN ''Model Regulation'':	UN1950, AEROSOLS, ENVIRONMENTALL
•	HAZARDOUS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.
- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220	Extrem	elv flami	mable gas.

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H301 Toxic if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- R11 Highly flammable.
- R12 Extremely flammable.
- R20/21 Harmful by inhalation and in contact with skin.
- R25 Toxic if swallowed.
- R36/37/38 Irritating to eyes, respiratory system and skin.
- R38 Irritating to skin.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmfull: may cause lung damage if swallowed
- *R67 Vapours may cause drowsiness and dizziness.*
- · Contact: Dipl.-Chem. G. Heller oder Dipl.-Ing. U. Voetter
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 9)

Version number 5 Printing date 18.12.2014 Revision: 18.12.2014

Trade name: MARABU Glitterspray

ICAO: International Civil Aviation Organization

(Contd. of page 8)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas: Gases under pressure: Compressed gas

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3 Acute Tox. 3: Acute toxicity, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2